


# WHITE LITHIUM GREASE



## LU™ 100



For use in medium pressure applications



NSF® Registered; H2 Rated (Lubricants with no contact) (Registration # 115074)



Minimum - Maximum operational temperature range: Low 20 °F (-7 °C) • High 275 °F (135 °C)



HMIS Hazard Rating: Health (2) • Flammability (4) • Reactivity (0)



National Lubricating Grease Institute Rating: 2

- Inhibits corrosion
- Works from 20°F to +275°F
- Non-melting



PRESERVE. PROTECT. PREVENT.™

Sprayon® LU™ 100 White Lithium Grease is a high solids white grease that provides excellent lubrication for metal-to-metal applications. Ideal for use on chains, gears, drives, hinges, etc. Excellent corrosion inhibitor for unpainted metal. It's clinging, no drip properties make it ideal for use on overhead applications and vertical surfaces.

## USES

- Chains
- Gears
- Drives
- Hinges
- Garage Door Guides

## LUBRICANTS

### APPLICATION

Maximum performance is achieved when the metal surfaces to be protected are clean, dry and free of rust, oil and mill scale. Product should be sprayed in a well ventilated area. Sprays best at room temperature. Shake well before using. Spray at a distance of 10" to 12" from surface.

### PERFORMANCE

**PLASTIC SAFE:** Yes

**TEMPERATURE RANGE:**

**LOW:** -20°F

**HIGH:** 275°F

**LOAD CAPACITY:** Medium

- NSF Registration Number 115074; H2 Rated
- Penetrant
- Water-Displacer
- Rust Inhibitor
- High solids content assures long lasting lubrication.
- Will not drip or run, even on vertical surfaces.
- Equipped with an extension tube for hard-to-reach areas.

### PROPERTIES

**APPEARANCE:** Off-white opaque

**ODOR:** Petroleum

**PROPELLANT:** Hydrocarbon

**WT./GAL.:** 5.77

**SPECIFIC GRAVITY:** 0.69

**VISCOSITY:** N.G.L.I. 2

**PAINTABLE:** No

**% VOC AEROSOL:** 65.00%

**V.O.C. COMPLIANT CALIFORNIA:** Yes

**V.O.C. COMPLIANT OTC STATES:** Yes

**FLAMMABLE:** Yes

**FLASH POINT:** <0°F

**HAZARD RATING:** 2,4,0

**SHELF LIFE:** 3 years from date of manufacture



LU100

### PACKAGING

**Stock #:** S00100

**UPC Code:** 0-75577-90100-5

**Fill Wt.:** 11 oz.

**Per Case:** 12

**Carton Dimensions:**

L 11.13" x W 8.44" x H 8.38"

### SHIPPING

Refer to section 14 of the material safety data sheet for proper transport information and labeling.

### RESOURCES

**MSDS/EDS/PRODUCT DATA SHEETS:**

sprayon.com

**CUSTOMER SERVICE:**

1-800-777-2966

**TECHNICAL INFORMATION:**

1-800-251-2486



© 2010 Sprayon® Products Made in U.S.A.

Distributed by:

PRESERVE. PROTECT. PREVENT.



**Sprayon® Products**

101 Prospect Ave. NW  
Cleveland, OH 44115  
Sprayon.com  
1-800-777-2966

310-PDS-LU100