

**SAFETY DATA SHEET** 

238 Ultra Supreme NLGI Grades 1, 2 and 3

## Section 1. Identification

GHS product identifier	: 238 Ultra Supreme NLGI Grades 1, 2 and 3
Other means of identification	: Not available.
Product type	: Liquid.
Identified uses	
Extreme pressure lubrication	ng grease.
Supplier's details	: Schaeffer Mfg. Company 102 Barton Street Saint Louis, Missouri 63104 Tel: 314-865-4100 Fax: 314-865-4107 Toll Free: 1-800-325-9962 E-Mail: safety@schaefferoil.com Web: http://www.schaefferoil.com
Emergency telephone	: +1 314 865-4105 (24-hour response number)

Emergency telephone number (with hours of operation)

## Section 2. Hazards identification

OSHA/HCS status	: While this material is not considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200), this SDS contains valuable information critical to the safe handling and proper use of the product. This SDS should be retained and available for employees and other users of this product.
Classification of the substance or mixture	: Not classified.
GHS label elements	
Signal word	: No signal word.
Hazard statements	: No known significant effects or critical hazards.
Precautionary statements	
Prevention	: Not applicable.
Response	: Not applicable.
Storage	: Not applicable.
Disposal	: Not applicable.
Hazards not otherwise classified	: None known.

### Section 3. Composition/information on ingredients

Substance/mixture

```
: Mixture
```

Ingredient name	%	CAS number
Base Oil(s)(*)	60 - 100	See below.
Phosphoric acid, sodium salt, hydrate	1 - 5	10101-89-0
Antimony, dialkyl dithiocarbamate	1 - 5	15890-25-2
1-Decene, homopolymer, hydrogenated	1 - 5	68037-01-4

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

#### Occupational exposure limits, if available, are listed in Section 8.

Base oil(s) contained in this material may be described by one or more of the following CAS Nos.: 64742-01-4, 64742-58-1, 64742-62-7, 64742-65-0.

### Section 4. First aid measures

#### **Description of necessary first aid measures**

Eye contact	mediately flush eyes with plenty of water, occasionally lifting the upper and lower relids. Check for and remove any contact lenses. Get medical attention if irritation ccurs.	ı
Inhalation	emove victim to fresh air and keep at rest in a position comfortable for breathing. edical attention if symptoms occur. In case of inhalation of decomposition produc fire, symptoms may be delayed. The exposed person may need to be kept under edical surveillance for 48 hours.	ts in
Skin contact	ush contaminated skin with plenty of water. Get medical attention if symptoms oc	cur.
Ingestion	ash out mouth with water. Remove victim to fresh air and keep at rest in a position omfortable for breathing. If material has been swallowed and the exposed person onscious, give small quantities of water to drink. Do not induce vomiting unless rected to do so by medical personnel. Get medical attention if symptoms occur.	

Most important symptoms/effects, acute and delayed		
Potential acute health effects		
Eye contact	: No known significant effects or critical hazards.	
Inhalation	: Exposure to decomposition products may cause a health hazard. Serious effects may be delayed following exposure.	
Skin contact	: No known significant effects or critical hazards.	
Ingestion	: No known significant effects or critical hazards.	
Over-exposure signs/symptoms		
Eye contact	: No known significant effects or critical hazards.	
Inhalation	: No known significant effects or critical hazards.	
Skin contact	: No known significant effects or critical hazards.	
Ingestion	: No known significant effects or critical hazards.	
Indication of immediate med	dical attention and special treatment needed, if necessary	
Notes to physician	<ul> <li>In case of inhalation of decomposition products in a fire, symptoms may be delayed.</li> <li>The exposed person may need to be kept under medical surveillance for 48 hours.</li> </ul>	
Specific treatments	: No specific treatment.	
Protection of first-aiders	: No action shall be taken involving any personal risk or without suitable training.	

## Section 5. Fire-fighting measures

Extinguishing media	
Suitable extinguishing media	: Use an extinguishing agent suitable for the surrounding fire.
Unsuitable extinguishing media	: None known.
Specific hazards arising from the chemical	: No specific fire or explosion hazard.
Hazardous thermal decomposition products	: Decomposition products may include the following materials: carbon dioxide carbon monoxide nitrogen oxides Sulfur oxides phosphorus oxides metal oxide/oxides
Special protective actions for fire-fighters	: No special measures are required.
Special protective equipment for fire-fighters	: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

## Section 6. Accidental release measures

#### Personal precautions, protective equipment and emergency procedures

For non-emergency personnel	:	No action shall be taken involving any personal risk or without suitable training. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Put on appropriate personal protective equipment.
For emergency responders	:	If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
Environmental precautions	:	Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. U.S.A. regulations may require reporting spills of this material that could reach any surface waters. Report spills to all applicable Federal, State, Provincial and local authorities and/or the United States National Response Center at (800) 424-8802 as appropriate or required.
Methods and materials for co	nt	ainment and cleaning up
One all a will	_	Oten leals if without risk. May a containers from anill area. Also should with an inert day

Small spill :	Stop leak if without risk. Move containers from spill area. Absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
Large spill :	Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

## Section 7. Handling and storage

Precautions for safe handling		
Protective measures	ut on appropriate personal protective equipment (see Section 8).	
Advice on general occupational hygiene	ating, drinking and smoking should be prohibited in areas where this mate andled, stored and processed. Workers should wash hands and face befor rinking and smoking. See also Section 8 for additional information on hygine asures.	ore eating,
Conditions for safe storage, including any incompatibilities	tore in accordance with local regulations. Store in original container prote- rect sunlight in a dry, cool and well-ventilated area, away from incompatib see Section 10) and food and drink. Keep container tightly closed and sea eady for use. Containers that have been opened must be carefully reseale oright to prevent leakage. Do not store in unlabeled containers. Use appr ontainment to avoid environmental contamination.	le materials led until ed and kept

### Section 8. Exposure controls/personal protection

#### **Control parameters**

#### **Occupational exposure limits**

Ingredient name	Exposure limits
Base Oil(s)(*) Antimony, dialkyl dithiocarbamate	NIOSH REL (United States, 10/2013).         TWA: 5 mg/m³ 10 hours. Form: Mist         STEL: 10 mg/m³ 15 minutes. Form: Mist         ACGIH TLV (United States).         TWA: 5 mg/m³ Form: Oil mist.         STEL: 10 mg/m³ Form: Oil mist.         OSHA PEL (United States).         TWA: 5 mg/m³ Form: Oil mist.         OSHA PEL (United States).         TWA: 5 mg/m³ Form: Oil mist.         OSHA PEL (United States, 4/2014).         TWA: 0.5 mg/m³, (as Sb) 8 hours.         OSHA PEL (United States, 2/2013).         TWA: 0.5 mg/m³, (as Sb) 8 hours.         NIOSH REL (United States, 10/2013).         TWA: 0.5 mg/m³, (as Sb) 10 hours.
ppropriate engineering ontrols	: Good general ventilation should be sufficient to control worker exposure to airborne contaminants.
nvironmental exposure	· Emissions from ventilation or work process equipment should be checked to ensure

**Environmental exposure controls** : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation.

Individual protection measures

Hygiene measures	: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
Eye/face protection	<ul> <li>Wear eye protection such as safety glasses, chemical goggles, or face shields if engineering controls or work practices are not adequate to prevent eye contact.</li> </ul>
Skin protection	
Hand protection	: Use nitrile or oil resistant gloves.
Body protection	<ul> <li>Personal protective clothing such as gloves, aprons, boots and complete facial protection should be selected based on the task being performed and the risks involved. Users should determine acceptable performance characteristics of protective clothing. Consider physical requirements and other substances present when selecting protective clothing.</li> </ul>

## Section 8. Exposure controls/personal protection

Other skin protection	: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved.
Respiratory protection	: If a risk assessment indicates that respiratory protection is required, use a properly fitted, air-purifying or supplied air respirator that complies with an approved standard. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

## Section 9. Physical and chemical properties

<u>Appearance</u>		
Physical state	:	Semi-solid. Grease.
Color	:	Black.
Odor	:	Mild petroleum.
Odor threshold	1	Not available.
рН	1	Not applicable.
Melting point/ Dropping Point	:	Not available.
Boiling point	1	>300°C (>572°F)
Flash point	1	Open cup: 268 to 277°C (514.4 to 530.6°F) [Cleveland.]
Evaporation rate	1	Not available.
Flammability (solid, gas)	1	Not available.
Lower and upper explosive (flammable) limits	:	Not available.
Vapor pressure	1	Not available.
Vapor density	1	>1 [Air = 1]
Relative density	1	1.02
Solubility	1	Negligible in water.
Partition coefficient: n- octanol/water	1	Not available.
Auto-ignition temperature	1	Not available.
Decomposition temperature	1	Not available.
Viscosity	1	Not available.
Volatility	1	Negligible.
VOC content	1	Not available.

# Section 10. Stability and reactivity

Reactivity	:	No specific test data related to reactivity available for this product or its ingredients.
Chemical stability	:	This material is considered stable under normal ambient and aniticpated storage and handling condtitions of temperature and pressure.
Possibility of hazardous reactions	:	Under normal conditions of storage and use, hazardous reactions will not occur.
Conditions to avoid	:	No specific data.
Incompatible materials	:	Reactive or incompatible with the following materials: Strong acids, bases and oxidizers.

## Section 10. Stability and reactivity

Hazardous decomposition products

: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

### Section 11. Toxicological information

#### Information on toxicological effects

#### Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
Phosphoric acid, sodium salt, hydrate Antimony, dialkyl dithiocarbamate	LD50 Oral LD50 Dermal LD50 Oral	Rabbit	7400 mg/kg 16000 mg/kg 16400 mg/kg	

#### Irritation/Corrosion

There is no data available.

#### Sensitization

There is no data available.

#### **Carcinogenicity**

There is no data available.

#### Specific target organ toxicity (single exposure)

Name	Category	Route of exposure	Target organs
Phosphoric acid, sodium salt, hydrate	Category 3	Not applicable.	Respiratory tract irritation

#### Specific target organ toxicity (repeated exposure)

There is no data available.

#### Aspiration hazard

Name	Result
1-Decene, homopolymer, hydrogenated	ASPIRATION HAZARD - Category 1

Information on the likely routes of exposure	: Dermal contact. Eye contact. Inhalation. Ingestion.
Potential acute health effect	<u>S</u>
Eye contact	: No known significant effects or critical hazards.
Inhalation	: Exposure to decomposition products may cause a health hazard. Serious effects may be delayed following exposure.
Skin contact	: No known significant effects or critical hazards.
Ingestion	: No known significant effects or critical hazards.
Symptoms related to the phy Eye contact Inhalation Skin contact Ingestion	<ul> <li>vsical, chemical and toxicological characteristics</li> <li>No known significant effects or critical hazards.</li> </ul>
Delayed and immediate effe	cts and also chronic effects from short and long term exposure
Short term exposure Potential immediate effects	: No known significant effects or critical hazards.

**Potential delayed effects** : No known significant effects or critical hazards.

### Section 11. Toxicological information

Long term exposure	
Potential immediate effects	: No known significant effects or critical hazards.
Potential delayed effects	: No known significant effects or critical hazards.
Potential chronic health effe	ects
General	: No known significant effects or critical hazards.
Carcinogenicity	: No known significant effects or critical hazards.
Mutagenicity	: No known significant effects or critical hazards.
Teratogenicity	: No known significant effects or critical hazards.
Developmental effects	: No known significant effects or critical hazards.
Fertility effects	: No known significant effects or critical hazards.

#### Numerical measures of toxicity

Acute toxicity estimates

There is no data available.

### Section 12. Ecological information

#### **Toxicity**

There is no data available.

#### Persistence and degradability

There is no data available.

#### **Bioaccumulative potential**

Product/ingredient name	LogPow	BCF	Potential
1-Decene, homopolymer, hydrogenated	>6.5	-	high

#### **Mobility in soil**

Soil/water partition coefficient (Koc)

: Not available.

Other adverse effects

: No known significant effects or critical hazards.

### Section 13. Disposal considerations

**Disposal methods** : The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling empty containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

### Section 14. Transport information

	DOT Classification	IMDG	ΙΑΤΑ
	DOT Classification	INDG	
UN number	Not regulated.	Not regulated.	Not regulated.
UN proper shipping name	-	-	-
Transport hazard class(es)	-	-	-
Packing group	-	-	-
Environmental hazards	No.	No.	No.
Additional information	-	-	-

**AERG** : Not applicable

Special precautions for user : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Transport in bulk according : Not available. to Annex II of MARPOL 73/78 and the IBC Code

### Section 15. Regulatory information

U.S. Federal regulations	: TSCA 8(a) CDR Exempt/Partial exemption: Not determined
	United States inventory (TSCA 8b): All components are listed or exempted.
	Clean Water Act (CWA) 307: Antimony, dialkyl dithiocarbamate
	Clean Water Act (CWA) 311: Phosphoric acid, sodium salt, hydrate; Sodium hydroxide
Clean Air Act Section 112 (b) Hazardous Air Pollutants (HAPs)	: Listed
Clean Air Act Section 602 Class I Substances	: Not listed
Clean Air Act Section 602 Class II Substances	: Not listed
DEA List I Chemicals (Precursor Chemicals)	: Not listed
DEA List II Chemicals (Essential Chemicals)	: Not listed
<u>SARA 302/304</u>	
Composition/information	on ingredients
No products were found.	
SARA 304 RQ	: Not applicable.

### Section 15. Regulatory information

### SARA 311/312

Classification

: Not applicable.

Composition/information on ingredients

Name	%	hazard	Sudden release of pressure		Immediate (acute) health hazard	Delayed (chronic) health hazard
Phosphoric acid, sodium salt, hydrate	1 - 5	No.	No.	No.	Yes.	No.

#### **SARA 313**

	Product name	CAS number	%
Form R - Reporting requirements	Antimony, dialkyl dithiocarbamate	15890-25-2	1 - 5
Supplier notification	Antimony, dialkyl dithiocarbamate	15890-25-2	1 - 5

SARA 313 notifications must not be detached from the SDS and any copying and redistribution of the SDS shall include copying and redistribution of the notice attached to copies of the SDS subsequently redistributed.

#### **State regulations**

Massachusetts	: The following components are listed: Molybdenum disulphide; Phosphoric acid, sodium salt, hydrate
New York	: The following components are listed: Phosphoric acid, sodium salt, hydrate
New Jersey	<ul> <li>The following components are listed: Residual oils (petroleum), solvent-dewaxed; Residual oils (petroleum), solvent-refined; Distillates (petroleum), solvent-dewaxed heavy paraffinic; Antimony, dialkyl dithiocarbamate</li> </ul>
Pennsylvania	<ul> <li>The following components are listed: ALUMINUM SOLUBLE SALTS; Antimony, dialkyl dithiocarbamate; Phosphoric acid, sodium salt, hydrate</li> </ul>

#### California Prop. 65

WARNING: This product contains less than 0.1% of a chemical known to the State of California to cause cancer.

Ingredient name	Cancer		No significant risk level	Maximum acceptable dosage level
Crystalline silica, quartz	Yes.	No.	No.	No.

### Section 16. Other information

#### Hazardous Material Information System (U.S.A.)

#### Health: 1 Flammability: 1 Physical hazards: 0

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks Although HMIS® ratings are not required on SDSs under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered mark of the National Paint & Coatings Association (NPCA). HMIS® materials may be purchased exclusively from J. J. Keller.

The customer is responsible for determining the PPE code for this material.

National Fire Protection Association (U.S.A.)

#### Health: 1 Flammability: 1 Instability: 0

Reprinted with permission from NFPA 704-2001, Identification of the Hazards of Materials for Emergency Response Copyright ©1997, National Fire Protection Association, Quincy, MA 02269. This reprinted material is not the complete and official position of the National Fire Protection Association, on the referenced subject which is represented only by the standard in its entirety.

Copyright ©2001, National Fire Protection Association, Quincy, MA 02269. This warning system is intended to be interpreted and applied only by properly trained individuals to identify fire, health and reactivity hazards of chemicals. The user is referred to certain limited number of chemicals with recommended classifications in NFPA 49 and NFPA 325, which would be used as a guideline only. Whether the chemicals are classified by NFPA or not, anyone using the 704 systems to classify chemicals does so at their own risk.

### Section 16. Other information

US Tariff Heading Number	: 2710.19.3750
Schedule B Code	: 2710.19.3750
<u>History</u>	
Date of issue mm/dd/yyyy	: 04/15/2015
Version	: 1
Prepared by	: KMK Regulatory Services Inc.

Although the information and recommendations set forth herein (hereafter referred to as information) are presented in good faith and believed to be accurate and factual as of the date hereof, Schaeffer Mfg. Company makes no representation as to the completeness or accuracy thereof. Information is supplied upon the condition that the person receiving the same will make their own determination as to its safety and suitability for their purposes prior to use. In no event will Schaeffer Mfg. Company be responsible for damages of any natures whatsoever resulting from the use or reliance upon information. No representation or warranty, either expressed or implied, of merchantability or fitness for a particular purpose is made with respect to information of the product to which the information refers. Compliance with all applicable federal, state, and local regulations remains the responsibility of the user.



KMK Regulatory ServicesTel : +1-888-GHS-7769 (447-7769) / +1-450-GHS-7767 (447-7767)www.kmkregservices.comwww.askdrluc.comwww.smkregservices.comwww.askdrluc.com

10/10