



TECHNICAL DATA

102 Barton Street, St. Louis, Missouri 63104

In-State (314) 865-4100/Out of State 800-325-9962/Fax (314) 865-4107 <http://www.schaefferoil.com>

#131C SOYULTRA[®] GASOLINE FUEL ADDITIVE

SoyUltra[®] Gasoline Fuel additive is a concentrated multifunctional ashless gasoline additive that specially formulated for use in all types of gasoline and ethanol blends used in new and old two-stroke and four-stroke gasoline powered vehicles.

SoyUltra[®] Gasoline Fuel Additive contains a unique blend of methyl soyate bio-fuel derived from soybean oil and an ashless multifunctional additive package that incorporates the dual functionality of frictional modification and detergency. When used at the recommended treatment ratios this unique combination allows the SoyUltra[®] Gasoline Fuel Additive to provide the following premium performance benefits.

1. Clean up and keep clean performance to restore performance and maintain new performance.
2. Improved carburetor, fuel injector, engine induction system, intake valve and combustion chamber cleanliness.
3. Modification of existing injector deposits, allowing for their removal and safe passage into the combustion chamber where they can be burned.
4. Superb piston deposit control to reduce the risk of engine seizure.
5. Increased engine performance.
6. Smoother idling.
7. Improved drivability.
8. Better –than-New Fuel Economy. Not a restoration due to cleanliness.
9. Up to 2% improvement in fuel economy on new vehicles and up to 5% on older vehicles.
10. Fuel economy improvements with continued use.
11. Up to 40% increase in fuel lubricity.
12. Excellent anti-wear protection of the fuel injectors and fuel pumps especially for those engines burning low sulfur gasoline, reformulated gasoline, oxygenated gasoline or ethanol blend gasoline.
13. Lubrication of upper cylinders, fuel pumps and injectors.
14. Supplemental ring and valve-train anti-wear protection.
15. Reduced emissions and particulates.
16. Stabilization of the fuel during long term storage

Continued on Next Page

TD-131C (Rev 10/09)

Treatment Ratio:

For Bulk Treatment of Gasoline:

Keep Clean Performance - One gallon of SoyUltra[®] Gasoline Fuel Additive to 2000 gallons of Gasoline

Clean-Up Performance – One gallon of SoyUltra[®] Gasoline Fuel Additive to 200 gallons of Gasoline

For Treatment of Vehicle Fuel Tanks:

1-12ounce bottle per tank-full (Generally 1-12 ounce bottle per 15 gallons of gasoline).

Typical Properties

Specific Gravity @ 60°F	0.8899 – 0.09191
Flash Point °F/°C, Pensky Martin ASTM D-93	122°-135°/50° - 57°
Ash Content % wt. ASTM D-482	0%
% Nitrogen, %wt.	0.3%