

HIGH PERFORMANCE DRY LUBRICANT



LU™ 708

HIGH PRESSURE™ — For use in extreme pressure applications

CONTAINS P.T.F.E. — Contains P.T.F.E. (polytetrafluoroethylene)

572 300 °F ↔ °C — Minimum - Maximum operational temperature range: Low -40 °F (-40 °C) • High 572 °F (300 °C)

H 2 F 4 R 0 — HMIS Hazard Rating: Health (2) • Flammability (4) • Reactivity (0)

- Works from -40°F to +572°F
- Safe on most plastics
- Lowest coefficient of friction
- Formulated with P.T.F.E.



PRESERVE. PROTECT. PREVENT.™

Sprayon® LU™ 708 High Performance Dry Lubricant is a clean, non-oily, non-staining, versatile dry lubricant that functions from -40°F to +572°F. It is a chemically inert formula that dries quickly to a white film to show coverage. This product does not contain silicone or chlorinated solvents. The extremely low static coefficient of friction makes it a superb lubricant where low speeds and light loads are involved. LU™ 708 High Performance Dry Lubricant has great anti-stick properties for use as an effective release agent.

USES

- Metal extrusions
- Elastomers
- Locks and catches
- Spray booths
- Drawers & hinges
- Window guides
- Machine parts
- Conveyor belts
- Chutes and slides
- Tanks
- Industrial blenders
- Bins

Use as a Release Agent on: Synthetic fibers, cord, twine or rope & most plastics.



LU708

© 2010 Sprayon® Products Made in U.S.A.

LUBRICANTS

APPLICATION

Maximum performance is achieved when the metal surfaces to be protected are clean, dry and free of rust, oil and mill scale. Product should be sprayed in a well ventilated area. Sprays best at room temperature. Shake well before using. Spray at a distance of 10" to 14" from surface.

PERFORMANCE

PLASTIC SAFE: Yes

TEMPERATURE RANGE:

LOW: -40°F

HIGH: 572°F

LOAD CAPACITY: Light pressure

- Penetrant
- Water-Displacer
- Rust Inhibitor

PROPERTIES

APPEARANCE: Translucent white film

ODOR: Mild Solvent

PROPELLANT: Hydrocarbon

WT./GAL.: 5.31

SPECIFIC GRAVITY: 0.64

PAINTABLE: No

% VOC AEROSOL: 98.41%

V.O.C. COMPLIANT CALIFORNIA: Yes

V.O.C. COMPLIANT OTC STATES: Yes

FLAMMABLE: Yes

FLASH POINT: <0°F

HAZARD RATING: 2,4,0

SHELF LIFE: 3 years from date of manufacture

RESOURCES

MSDS/EDS/PRODUCT DATA SHEETS:

sprayon.com

CUSTOMER SERVICE:

1-800-777-2966

TECHNICAL INFORMATION:

1-800-251-2486

PACKAGING

Stock #: S00708

UPC Code: 0-75577-90708-3

Fill Wt.: 10 oz.

Per Case: 12

Carton Dimensions:

L 11.13" x W 8.44" x H 8.38"

SHIPPING

Refer to section 14 of the material safety data sheet for proper transport information and labeling.



Distributed by:

PRESERVE. PROTECT. PREVENT.



Sprayon® Products

101 Prospect Ave. NW
Cleveland, OH 44115
Sprayon.com
1-800-777-2966

310-PDS-LU708